Robot local navigation with learned social cost functions

Noé Pérez-Higueras¹, Rafael Ramón-Vigo¹, Fernando Caballero² and Luis Merino¹

¹School of Engineering, Pablo de Olavide University, Crta. Utrera km 1, Seville, Spain

²Dpt. of System Engineering and Automation, University of Seville, Camino de los Descubrimientos s/n, Seville, Spain {noeperez, rramvig, lmercab}@upo.es, fcaballero@us.es

Keywords: Robot Navigation, Social Robots, Inverse Reinforcement Learning, Learning from Demonstrations

Abstract: Robot navigation in human environments is an active research area that poses serious challenges. Among them, human-awareness has gain lot of attention in the last years due to its important role in human safety and robot acceptance. The proposed robot navigation system extends state of the navigation schemes with some social skills in order to naturally integrate the robot motion in crowded areas. Learning has been proposed as a more principled way of estimating the insights of human social interactions. To do this, inverse reinforcement learning is used to derive social cost functions by observing persons walking through the streets. Our objective is to incorporate such costs into the robot navigation stack in order to "emulate" these human interactions. In order to alleviate the complexity, the system is focused on learning an adequate cost function to be applied at the local navigation level, thus providing direct low-level controls to the robot. The paper presents an analysis of the results in a robot navigating in challenging real scenarios, analyzing and comparing this approach with other algorithms.

1 INTRODUCTION

The Fun Robotic Outdoor Guide (FROG) FP7 project¹ aims to deploy a guiding robot in touristic sites. While robot guides has been developed for more than a decade (Thrun et al., 2000; Siegwart et al., 2003), the project considers as new contributions the development of social behaviors and a wining robot personality by integrating social feedback, as well as the robust operation in outdoors crowded scenarios. The project aims to demonstrate the operation of the robot in the Lisbon City Zoo and the Royal Alcazar in Seville (see Fig. 1). Acting in these crowded scenarios (the Royal Alcazar may have around 5000 visits per day, totaling 1.5 million-visitors per year) involves not only ensuring a safe and efficient navigation but also social interaction and social awareness when performing the robot tasks.

The creation of motion plans for robots that share space with humans in dynamic environments is a subject of intense investigation in the robotics field. Robots must respect human social conventions, guarantee the comfort of surrounding persons, and maintain legibility, so humans can understand the robots intentions (Kruse et al., 2013). This human aware navigation involves different fields as human percep-



Figure 1: The FROG project aims to deploy a guiding robot with a fun personality, considering social feedback, in the Royal Alcazar of Seville and the Zoo of Lisbon. A typical situation of the first scenario is presented here.

tion, cognitive models and motion planning. Furthermore, these considerations have to be taken into account in the entire robot planning and navigation stack, from task planning (Alili et al., 2009), task supervision and execution (Clodic et al., 2008) to path planning and execution (Sisbot et al., 2007; Tipaldi and Arras, 2011; Trautman and Krause, 2010).

Social awareness requires that a robot is able to detect persons, estimate their poses and differentiate them from static and dynamic obstacles. Laser rangefinders have been used for person detection and tracking (Arras et al., 2008; Carballo et al., 2010).

¹http://www.frogrobot.eu

Other common approach is the use of vision. In the FROG robot, in addition to laser rangefinders, a stereo vision system is able to provide persons positions and orientations in real time (Enzweiler and Gavrila, 2008; Keller et al., 2011).

Once the robot has information about the surrounding persons, the navigation stack should consider them in a different way than other obstacles in the environment to achieve a socially normative navigation. Current path planners will not solve the social navigation problem, as planners try to minimize time or length, which does not translate to social paths in general. This requires determining costs related to social compliance. Some authors (Sisbot et al., 2007; Kirby et al., 2010) have included costs and constraints related to human-awareness into planners to obtain socially acceptable paths, but these costs are preprogrammed. However, hard-coded social behaviours may be inappropriate (Feil-Seifer and Mataric, 2011).

Thus, learning these costs and models from data seems a more principled approach. In the last years, several contributions have been presented in this direction: supervised learning is used in (Trautman and Krause, 2010) to learn appropriate human motion prediction models that take into account human-robot interaction when navigating in crowded scenarios. Unsupervised learning is used by (Luber et al., 2012) to determine socially-normative motion prototypes, which are then employed to infer social costs when planning paths.

A potential approach is learning from demonstrations (Argali et al., 2009): an expert indicates the robot how it should navigate among humans. One way to implement it is through inverse reinforcement learning (Abbeel and Ng, 2004), in which a reward (or cost) function is recovered from the expert behavior, and then used to obtain a corresponding robot policy. While a direct policy from state to actions may be also learned from the examples, learning a reward function allows to transfer the task to other situations.

In (Henry et al., 2010), the authors present a path planner based on inverse reinforcement learning. As the planner is learned for exemplary trajectories involving interaction, it is also aware of typical social behaviors. In this paper we also consider inverse reinforcement learning for social navigation. However, while in (Henry et al., 2010) the costs are used to path plans, here they are employed to learn local execution policies, thus providing direct control of the robot. This can be combined with other planning techniques at higher levels, while alleviating the complexity associated to learning. Furthermore, a dataset of person motion is employed here to learn the cost functions. In the paper, we analyze and compare this approach



Figure 2: Robot platform, placement and field of view of the sensors. Green planes denote the front and rear laser scanner planes. Orange plane stands for the 45° tilted laser scanner. Red fields denote the field of view of the front stereo camera and back camera. Blue areas stand for sonar sensing areas.

with several other possibilities.

The structure of the paper is as follows: next section describes the robotic platform used and explains the navigation stack implemented in the robot. Then, Section 3 is where the learning approach is detailed. Section 4 deals with the evaluation through experiments, finishing with the conclusions and future open lines.

2 ROBOT NAVIGATION

2.1 FROG Robot

Figure 2 shows a picture of the FROG robot. It consists of a skid-steering platform, with 4 wheels adapted to the scenarios considered in the project. The platform has been developed by the Portuguese company IDMind. It has an autonomy of two to four hours depending on the type of ground and the number of embedded PCs running, up to three. The robot weights 80Kg approximately and its maximum velocity is 1.6 m/s (software limited to 0.8 m/s).

The robot is equipped with a wide range of sensors for safety, localization and navigation. Among them, the following sensors are considered for person detection and navigation:

- Odometry is computed by reading encoders and angular velocities from an MTi-G IMU from XSens.
- Three laser rangefinders are considered. Two deployed horizontally in the rear and in the front of the robot, employed for localization, obstacle

avoidance and person detection. The third laser is placed in front of the robot and tilted 45° , it is used for 3D obstacle avoidance.

- A stereo camera pair is employed for person detection, pose estimation and 3D perception.
- An additional camera is used for low-range affective computing of the interacting persons.
- A sonar ring surrounding the robot for obstacle detection.

In the FROG robot the sensors are disposed in order to cover as much area as possible around it. The frontal and real lasers cover a total angle of 360° around the robot. Moreover, the sonars are employed to detect obstacles in the lateral areas of the robot which the lasers can not cover as well as elements at different height than the lasers.

A tilted laser was also installed in the robot in order to detect short range obstacles not visible by the frontal lasers (obstacles upper or below their scan plane). The laser is placed right below the screen and tilted 45° approximately. This configuration allows for detecting close objects in front of the robot.

Regarding the key-aspect of person detection, the main sensor considered is the stereo camera pair which is used by the People Detection algorithm (Enzweiler and Gavrila, 2008; Keller et al., 2011). This algorithm has demonstrated to be flexible and accurate enough to detect persons in front of the robot. However, the limited field of view of the stereo cameras used as image input for this algorithm limits the amount of information served to the navigation stack and, more importantly, do not provide person information in the back of the robot.

A second source of information has been added to increase the detection area for persons, a 2D laserbased algorithm for persons detection (Arras et al., 2008). This algorithm is not as accurate as the vision algorithm but it is reliable enough to provide good estimations of persons around the robot. We use the front and rear lasers as inputs for this algorithm, so we are able to detect persons in 360° around the robot.

2.2 Structure of the navigation stack

The navigation stack of the FROG robot follows the classical separation between a global path planner and a local path execution module (see Fig. 3). The global planner employs the robot global pose and global models of the obstacles (and potentially other models) in order to determine a path to the goal. The local planner receives the global path and tries to follow it, by considering the most up to date sensorial information on the robot frame. This local planner



Figure 3: The navigation stack consists of a global planner, acting on global models; and a local planner acting on the most up to date information at a higher frequency.

generates the controls (angular and linear velocities) commanded to the robot platform.

The current implementation of the navigation stack extends the Robot Operating System (ROS) (Marder-Eppstein et al., 2010) navigation architecture. In this paper we are mainly concerned with adapting the local planner, although significant modifications have been carried out to adapt the global planner to the FROG requirements. The global path planner is based on a Dijkstra's algorithm to search through the available working area and find the best path. As future work we plan to consider also social constraints at this level.

We consider as local planner an extension of the Trajectory Rollout algorithm (Gerkey and Konolige, 2008). The algorithm has been almost reimplemented considering computational efficiency as a major constraints. This controller predicts possible trajectories with a discrete-time simulation over a receding horizon. To ensure safe and feasible motion, the robot's kinodynamic constrains and accelerations have to be indicated correctly. The controller choses the best trajectory among the predicted trajectories by evaluating different cost functions such as distance to the global path, distance to local goal or obstacle cost among others. These different cost functions are combined by using a convex combination and allow to balance the robot different goals. We modify this technique to include additional cost terms considering social awareness and the position of the persons, which are then learned from data.

To compute the global path and to evaluate the different trajectories to follow the path locally, two 2D grid maps are used. Each map cell of the grid map contains relevant information for motion, such as the presence of an obstacle, or membership in a recognized path. For global planning, the grid map is built from the information of the predefined navigation map along with the sensors data. For local planning, another 2D grid map is built just from sensors data. This is a rectangular grid map around the robot.

3 LEARNING THE SOCIAL COST FUNCTION

As indicated above, it is hypothesized that learning the mentioned cost functions by observing how humans navigate among themselves will lead to socially normative behaviors.

The learning of the cost function is accomplished by using inverse reinforcement learning (IRL, (Abbeel and Ng, 2004)). IRL assumes that the expert from which we want to learn is modeled by a Markov Decision Process (MDP). Formally, a discrete MDP is defined by the tuple $\langle S, A, T, R, D, \gamma \rangle$. The state space is the finite set of possible states $s \in S$; the action space is defined as the finite set of possible actions $a \in A$. At every step, an action is taken and a reward is given (or cost is incurred). After performing an action a, the state transition is modeled by the conditional probability function T(s', a, s) = p(s'|a, s). At every time instant then the state is observed. The reward obtained at each step is denoted R(s,a). A function $a = \pi(s)$ that maps an state to an action is called a policy. A policy that maximizes the sum of expected rewards, or *value*, earned during D time steps $E[\sum_{t=0}^{D} \gamma R(s,a)]$ is called an *optimal* policy. To ensure that the sum is finite when $D \rightarrow \infty$, rewards are weighted by a discount factor $\gamma \in [0, 1)$.

The objective of IRL is to determine the reward function R(s,a) that the expert is following by observing the expert acting in the real world, assuming that it is executing a policy according to the given MDP. In many cases, the reward function can be assumed to depend on a set of features $\theta(s)$, which are functions of the state.

The idea of using IRL for robot navigation has been proposed by Henry et al., (Henry et al., 2010) to estimate cost functions for robot path planning. Here, there are several differences with respect to this approach, that will be described in the next sections.

3.1 Models

The most relevant aspect of the approach is to define the MDP model, and, in particular, the state space and the features on which the reward function is depending on. This constitute the main hypothesis considered here.

In addition, in order to alleviate the complexity of the problem, we use two models. One just considering features concerning pairwise relative motions between two persons, and another one, based on high level features like person densities in different regions in front of the robot. We evaluate the models in section 4.



Figure 4: The state of model 1 is defined as the relative pose of the person with respect to the robot. The actions (linear and angular speeds) affect how this state evolves.



Figure 5: The state in the model 2 is defined with the densities $(persons/m^2)$ in the three regions in front of the robot.

3.1.1 Model 1

In principle, the actions of a person (or robot) navigating among other people will depend on the state of all the persons close to the robot, plus many other factors, like obstacles and the person goal. However, considering all the persons will lead to a large (and timevariant in size) state space. In (Henry et al., 2010), this is tackled by considering the density and flow direction as features, and using them at the path planning level.

Here, the model considers the generation of the velocity controls of the vehicle. Contrary to (Henry et al., 2010), we parameterize the state on the local robot/expert frame. This allows reducing the complexity of the problem. Furthermore, in the model we consider just pairwise relative motions between two persons (a robot and a person). The state is then defined by the relative position and orientation of the person with respect to the robot, encoded as $s = (d \ \theta \ \phi)^T$ (see Fig. 4). As the parameterization is local, the pose of the robot is not considered into the state. The effects of the actions on the state are modeled by using simple kinematic equations, and are considered to be deterministic. Uncertainties are added on the person motion part, sampling several

variations on the linear and angular velocities of the person and determining its future position. This way, the transition function T(s', a, s) is determined. One hypothesis that will be analyzed in this paper is if the model can be extrapolated to cases with more persons by means of the cost function learned applied to all the persons present in the scene.

3.1.2 Model 2

The second MDP model proposed is based on high level features to define the reward function. In particular, the person densities in different regions in front of the robot are considered to parametrize the state on the robot frame. We use the same area as in model 1, but in this case, we divide it in three independent regions; one in front of the robot and two on the left and right sides (see Fig. 5).

Therefore, the state is encoded as $s = (\rho_1 \ \rho_2 \ \rho_3)^T$. The density value for each region is divided in 5 bins of range 0.25 *persons/m²*, except the first bin that corresponds to value 0 of density. Then, the transition function T(s', a, s) is determined by considering how the densities in the regions are affected by the robot motion. In this case, the uncertainties are introduced in the new density values due to the inflow motion of persons and the outflow of persons in the regions.

The development of this model aims at complementing the first model in a simple way. The idea is to capture other navigation behaviors in crowded environments that the first model does not consider, as it only considers the closest pedestrian. We alleviate the complexity of the IRL problem and the computational cost by dividing the learning process into different reward functions. Thus, we do not add the new densities features into the previous model state in order to obtain a more complete (and complicated) model. Instead, we develop a new model considering only the densities features, and then obtaining the corresponding reward function. Then, we can use the reward function learned for model 1 and mix it with the new reward function obtained for the model of densities, model 2. The results will be showed in Sections 4.

3.1.3 Learning

We consider the algorithm Gaussian Process IRL (GPIRL) (Levine et al., 2011) for solving the IRL problem. The main difference with respect to other approaches is that it employs a Gaussian Process to learn a non-linear reward function over the feature space. Thus, the GP allows to extrapolate the learnt reward function to other state spaces within the domain of the features considered.



Figure 6: Example image of the pedestrian dataset used for learning. See (Pellegrini et al., 2009) for more details.

As a source of examples, the BIWI Walking Pedestrians dataset² has been used (Pellegrini et al., 2009). This dataset consists of a bird view of a outdoors urban environment, and is annotated with the positions and velocities of all persons and the corresponding timestamps (see Fig. 6).

In our case, we employ the dataset to gather the examples from experts in the task of navigating among persons. A set persons are selected as "experts" among the pedestrians that are moving in the dataset. For each point in the trajectory followed by the person we extract:

- The state for model 1 $s_i = (d \ \theta \ \phi)^T$ of the closest person within the local planning zone (6 meters in front and 2 meters at each side of the robot).
- In case of model 2. The state $s_i = (\rho_1 \quad \rho_2 \quad \rho_3)^T$.
- The action performed by the expert at the same time instant. In particular, the linear and angular velocities $a_i = (v \ \omega)^T$, in order to easily transfer them to the robot.

Thus, for each expert the trajectory $\{s_i, a_i\}_{i=1}^N$ is stored as one episode for the learning phase. The GPIRL algorithm uses a discrete MDP as model. Therefore, the state and actions spaces are discretized considering how experts and pedestrians behave in the dataset.

Finally, by using the previous examples extracted from the dataset as an input to the IRL algorithm, a reward (cost) function R(s,a) is obtained as a result, which associates a scalar value to each state (Ramon-Vigo et al., 2014). We use this value as a new cost in the local planning algorithm and its weight is tuned by hand.

²http://www.vision.ee.ethz.ch/datasets/

4 EXPERIMENTS

In this section we show actual experiments performed with the robotic platform, integrating the subsystems described above. In these experiments, the robot autonomously navigates from a starting point to a given waypoint, encountering persons in his path during the execution.

The experiments will evaluate the approach by comparing a classic local planner (Gerkey and Konolige, 2008) with the same planer augmented with the learned costs and the costs based on a classic Proxemics aproach (Hall, 1990; Kirby et al., 2009).

The results are compared using as metrics the total distance traveled towards the goal (TD), the time to execute the path and the minimum and average distances to the persons (Min PD and Mean PD respectively) along the path. They are shown along with their standard deviations. By computing the execution time and total distance traveled we can assess the effectiveness to reach the goal, while the distances to persons let us know how the personal space is conserved.

4.1 Experiments with static controlled pedestrians

In this set of experiments, the robot had to cross a controlled scenario with pedestrian standing, talking to each other. It is assumed an static scenario in the sense that people do not move from their initial position. We performed 4 runs for each approach, keeping the same configuration between the different runs.

We show the results for the basic navigation without "social component" (No social), results for the proxemics approach (Proxemics), results with the social cost obtained with the model 1 (One Ped), results with the model 1 generalization from one pedestrian to all (All Ped), results for model 2 (Densities) and finally, results taking into account the costs derivated for model 1 and model 2 (One Ped + Dens). Table 1 summarizes the metrics for each approach:

- No social: the navigation without the social component tries to optimize time and distance traveled. It can be seen how the average and mean distances to pedestrians are the lowest of all the approaches.
- Proxemics: this classical approach improves a bit the results of the "No social" navigation, in the sense that the robot keeps itself farther from the personal space of the persons. Anyway, it performs a too significant avoidance when the robot is close to pedestrian which is consider unnecessary.

Table 1: Experimental results in a static scenario

	T (s)	TD (m)	Mean PD (m)	Min PD (m)
No social	50.65 ± 0.21	$21.76 \!\pm\! 0.29$	2.82 ± 0.06	0.82 ± 0.03
Proxemics	71.00 ± 1.55	21.09 ± 1.04	3.69 ± 1.69	1.05 ± 0.18
One Ped	54.28 ± 3.39	20.50 ± 0.22	5.19 ± 1.06	1.29 ± 0.18
All Ped	58.85 ± 0.21	22.68 ± 0.19	5.22 ± 1.69	1.69 ± 0.04
Densities	51.05 ± 0.92	24.53 ± 0.01	4.50 ± 0.21	0.87 ± 0.02
OnePed + Dens	53.27 ± 3.17	21.19 ± 1.56	4.00 ± 1.82	1.01 ± 0.29

- One pedestrian (model 1). The proxemics results are improved by this approach. It keeps a longer distance to the pedestrians than in the no social case, but the avoiding maneuvers are performed more in advance than in the proxemics case, which can be suitable for no-crowded scenarios. But the performance can degrade if there are several people surrounding the robot.
- All pedestrian. According to the results, taking into account all the pedestrian instead of just the closest, has a similar performance as in the previous case. These results can be different in experiments with more people. Anyway, we think that this generalization can not retrieve the necessary key aspects for a good navigation in crowded environments.
- Densities (model 2). In this case, the distances to the pedestrians are lower than the case of model 1 and its generalization. However, aspects like the orientation or the direction of motion of the pedestrian are not taken into account, which can lead to unwanted avoiding behaviors.
- One pedestrian + Densities (model 1 and model 2). This approach performs the avoiding maneuvers before than in the proxemics case without performing excessive avoidance. Moreover, it keeps a shorter distance to the pedestrians than just model 1 without being uncomfortable for them. We consider that this behavior can be suitable for crowded environments.

4.2 Experiments with dynamic controlled pedestrians

To perform these experiments we used the same scenario than before, but, in this case, the pedestrians were moving and crossing the area. As before, we performed 4 runs for each navigation approach, trying to repeat the pedestrians movement.

The setup of the controlled experiment is like follows: Two pedestrians walk opposite to robot direc-

	T (s)	TD (m)	Mean PD (m)	Min PD (m)
No social	59.22 ± 0.06	20.38 ± 0.29	2.31 ± 0.15	0.20 ± 0.09
Proxemics	68.44 ± 0.02	20.99 ± 0.68	2.59 ± 0.10	0.38 ± 0.04
One Ped	69.45 ± 7.01	21.85 ± 1.89	4.46 ± 0.19	0.20 ± 0.17
All Ped	61.20 ± 0.0	20.50 ± 0.0	2.49 ± 0.16	0.60 ± 0.12
Densities	65.26 ± 10.08	20.75 ± 0.24	2.56 ± 0.17	0.47 ± 0.16
OnePed + Dens	60.20 ± 1.81	20.36 ± 0.35	2.46 ± 0.10	0.33 ± 0.02

Table 2: Experimental results in a dynamic scenario

tion forcing it to avoid them. Then, other pedestrian cross in diagonal in front of the robot. Finally, two new pedestrians pass the robot on the left walking in the same direction as it.

The results are presented in Table 2. They are very similar to the results obtained in case of static pedestrians. Again, all the "social" approaches suggested improve the "no social" behavior. In this case, the model 1 (One Ped) seems to make some excessive avoiding maneuvers. However, the mixed approach of model 1 and model 2 seems to keep an acceptable distance to pedestrians in crowded environments and makes smooth avoiding maneuvers.

4.3 Experiments in target scenarios: Royal Alcazar of Seville

Another set of experiments were performed in the Alcazar of Seville, where the final demo of FROG project will take place. In this case, the social costs obtained from model 1 and 2 were employed (see Fig. 7).

The guided tour has a distance of 435 meters approximately, including the return path to the initial point, which involves a different route. During a week of testing, the tour was performed satisfactory twice a day, which gives a total of almost 4.5 kms of autonomous navigation in a very crowded scenario.

The social behavior of the robot was showed to be suitable in several cases. The robot is able to anticipate its movements performing smooth avoiding maneuvers when it detects people walking in the opposite direction.

5 CONCLUSIONS AND FUTURE WORK

The paper summarized the robot navigation system developed in the framework of the FROG project. An efficient and safe navigation system has been im-



Figure 7: Example of people detection system. On the left: typical situation at Royal Alcazar, with lot of people around the robot. On the right: localization of the robot, with 360° people detection (green cylinders).

plemented according to the FROG system specifications, paying special attention to the social interaction aspects of this navigation. We have presented an approach that uses inverse reinforcement learning to learn cost/reward functions from examples for the task of navigating among persons. Two simple models and the use of a public dataset to extract the learning samples are described.

All the different approaches are compared between them and the Proxemics approach. The results show that IRL can be used to transfer some human navigation behaviors into the low-level navigation controllers of a mobile robot. The robot local controller improves lightly the Proxemics performance and is able to anticipate smooth avoiding maneuvers when people is walking in opposite or almost parallel directions. However, the improvement is not very significant and the social costs do not retrieve all the key-insight involved in a social navigation in crowded environments. This may indicate that the local planner used is no able to find the best action in these cases.

As future work, we plan to record our own dataset which includes a richer variety of crossing behaviors between persons and other social constrains. Furthermore, new features can be added to the models like the persons flow direction. We will consider randomized planners, like RRTs (Rios-Martinez et al., 2011), as local planner. We will reason about social costs in the global path planning level. Besides, we plan to carry out a qualitative evaluation on the perception of the pedestrian regarding the different navigation modes described in the experimental section.

ACKNOWLEDGEMENTS

This work is partially funded by the European Commission 7th Framework Programme under grant agreement no. 288235 (FROG) and the project PAIS- MultiRobot, funded by the Junta de Andalucía (TIC-7390). The authors also thank the Lisbon Zoo and the Royal Alcázar in Seville for allowing to perform the experiment at their facilities.

REFERENCES

- Abbeel, P. and Ng, A. Y. (2004). Apprenticeship learning via inverse reinforcement learning. In *Proceedings of* the twenty-first international conference on Machine learning, ICML '04, pages 1–, New York, NY, USA. ACM.
- Alili, S., Warnier, M., Ali, M., and Alami, R. (2009). Planning and plan-execution for human-robot cooperative task achievement. In 19th International Conference on Automated Planning and Scheduling.
- Argali, B., Chernova, S., Veloso, M., and Browning, B. (2009). A survey of robot learning from demonstrations. *Robotics and Autonomous Systems*, 57:469– 483.
- Arras, K. O., Mozos, O. M., and Burgard, W. (2008). Using boosted features for the detection of people in 2d range data. In Proc. International Conference on Robotics and Automation, ICRA.
- Carballo, A., Ohya, A., and Yuta, S. (2010). People detection using range and intensity data from multi-layered laser range finders. In Proc. International Conference on Intelligent Robots and Systems, IROS, pages 5849– 5854.
- Clodic, A., Cao, H., Alili, S., Montreuil, V., Alami, R., and Chatila, R. (2008). SHARY: A Supervision System Adapted to Human-Robot Interaction. In Khatib, O., Kumar, V., and Pappas, G. J., editors, *Experimental Robotics, The Eleventh International Symposium, ISER 2008, July 13-16, 2008, Athens, Greece*, volume 54 of Springer Tracts in Advanced Robotics, pages 229–238. Springer.
- Enzweiler, M. and Gavrila, D. (2008). Integrated pedestrian classification and orientation estimation. In *Proc.* of the IEEE Conf. on Computer Vision and Pattern Recognition.
- Feil-Seifer, D. and Mataric, M. (2011). People-aware navigation for goal-oriented behavior involving a human partner. In Proceedings of the IEEE International Conference on Development and Learning (ICDL).
- Gerkey, B. and Konolige, K. (2008). Planning and control in unstructured terrain. In Workshop on Path Planning on Costmaps, Proceedings of the IEEE International Conference on Robotics and Automation.
- Hall, E. T. (1990). The Hidden Dimension. Anchor.
- Henry, P., Vollmer, C., Ferris, B., and Fox, D. (2010). Learning to navigate through crowded environments. In *ICRA'10*, pages 981–986.
- Keller, C., Enzweiler, M., Rohrbach, M., Llorca, D.-F., Schnörr, C., and Gavrila, D. (2011). The benefits of dense stereo for pedestrian detection. *IEEE Trans. on Intelligent Transportation Systems*, 12(4):1096–1106.

- Kirby, R., J. Forlizzi, J., and Simmons, R. (2010). Affective social robots. *Robotics and Autonomous Systems*, 58:322–332.
- Kirby, R., Simmons, R. G., and Forlizzi, J. (2009). Companion: A constraint-optimizing method for personacceptable navigation. In *RO-MAN*, pages 607–612. IEEE.
- Kruse, T., Pandey, A. K., Alami, R., and Kirsch, A. (2013). Human-aware robot navigation: A survey. *Robot. Auton. Syst.*, 61(12):1726–1743.
- Levine, S., Popovic, Z., and Koltun, V. (2011). Nonlinear inverse reinforcement learning with gaussian processes. In *Neural Information Processing Systems Conference*.
- Luber, M., Spinello, L., Silva, J., and Arras, K. (2012). Socially-aware robot navigation: A learning approach. In *IROS*, pages 797–803. IEEE.
- Marder-Eppstein, E., Berger, E., Foote, T., Gerkey, B. P., and Konolige, K. (2010). The Office Marathon: Robust Navigation in an Indoor Office Environment. In *International Conference on Robotics and Automation*.
- Pellegrini, S., Ess, A., Schindler, K., and van Gool, L. (2009). You'll never walk alone: Modeling social behavior for multi-target tracking. In *International Conference on Computer Vision*.
- Ramon-Vigo, R., Perez-Higueras, N., Caballero, F., and Merino, L. (2014). Transferring human navigation behaviors into a robot local planner. In *RO-MAN*. In Press.
- Rios-Martinez, J., Spalanzani, A., and Laugier, C. (2011). Understanding human interaction for probabilistic autonomous navigation using risk-rrt approach. In *Intelligent Robots and Systems (IROS), 2011 IEEE/RSJ International Conference on*, pages 2014–2019.
- Siegwart, R., Arras, K. O., Bouabdallah, S., Burnier, D., Froidevaux, G., Greppin, X., Jensen, B., Lorotte, A., Mayor, L., Meisser, M., Philippsen, R., Piguet, R., Ramel, G., Terrien, G., and Tomatis, N. (2003). Robox at Expo.02: A large-scale installation of personal robots. *Robotics and Autonomous Systems*, 42(3-4):203–222.
- Sisbot, E. A., Marin-Urias, L. F., Alami, R., and Siméon, T. (2007). A Human Aware Mobile Robot Motion Planner. *IEEE Transactions on Robotics*, 23(5):874–883.
- Thrun, S., Beetz, M., Bennewitz, M., Burgard, W., Cremers, A. B., Dellaert, F., Fox, D., and Hahnel, C. (2000). Probabilistic algorithms and the interactive museum tour-guide robot minerva. *The International Journal* of Robotics Research, 19:972–999.
- Tipaldi, G. D. and Arras, K. O. (2011). Planning Problems for Social Robots. In *Proceedings fo the Twenty-First Internacional Conference on Automated Planning and Scheduling*, pages 339–342.
- Trautman, P. and Krause, A. (2010). Unfreezing the robot: Navigation in dense, interacting crowds. In *IROS*, pages 797–803. IEEE.